

Kategorija: **AMD matične ploče**

Proizvođač: **Gigabyte**

Šifra: **B850M Aorus Elite**

Matična ploča AM5 Gigabyte B850M Aorus Elite WIFI 6

Matična ploča AM5 Gigabyte B850M Aorus Elite WIFI 6 Ice DDR5 DP/MI/M.2

Maloprodajna cena: 30.990,00 RSD

Web cena: 29.990,00 RSD

Ušteda: 1.000,00 RSD

Specifikacija

Procesorsko ležište (socket)	AMD AM5
Čipset	AMD B850
Tip memorije	DDR5
Memorijski slotovi	4
Podržane memorije	6.000MT/s (O.C.), 7.200MT/s (O.C.), 7.000MT/s (O.C.), 6.800MT/s (O.C.), 6.600MT/s (O.C.), 6.400MT/s (O.C.), 6.200MT/s (O.C.), 4.800MT/s, 7.600MT/s (O.C.), 5.600MT/s (O.C.), 8.000MT/S (O.C.), 7.800MT/s (O.C.), 8.200MT/s (O.C.), 5.800MT/s (O.C.), 4.400MT/s, 7.400MT/s (O.C.), 5.200MT/s (O.C.), 7.950MT/s (O.C), 7.900MT/s (O.C)
Maksimalna ukupna memorija	256GB
Ostale osobine	Podrška za Unbuffered ECC memoriju, Podrška za Extreme Memory Profile (XMP), Dvokanalni (Dual-channel) režim rada memorije, Podrška za non-ECC UDIMM memory, Podrška za AMD EXTended Profiles for Overclocking (EXPO)
PCI Express x16 slot	1x PCI Express 5.0 (x16 mode), 1x PCI Express 3.0 (x16 mode)
SATA priključci (ukupno)	4
SATA priključci	SATA III 6Gbps
Broj M.2 slotova	2
Podržani M.2 formati	1x 2280 / 22110 (podrška za PCIe 4.0 x4/x2 mod), 1x 2280 / 2580 / 22110 / 25110 (podrška za PCIe 5.0 x4/x2 mod)
RAID	RAID 0, RAID 1, RAID 10
Žična mreža (LAN)	2.5GBase-T (Gigabit)
Model	Realtek RTL8852CE
Wi-Fi	Da
Wi-Fi standard	Wi-Fi 6E (802.11ax)
Bluetooth	Da
Bluetooth verzija	5.3
Broj kanala	8 (7.1)
Model	Realtek

Napomena	High Definition
Broj DisplayPort priključaka	1
DisplayPort priključci	1x DisplayPort 1.4
Ukupno USB priključaka	12
Ukupno USB-C priključaka	1
USB-A priključci	2x USB 10Gbps (3.2 Gen 2), 4x USB 2.0, 5x USB 5Gbps (3.2 Gen 1)
USB-C priključci	1x USB 10Gbps (3.2 Gen 2)
RJ-45 (LAN)	1
Audio	2x 3.5mm, 1x S/PDIF optički
Ostali priključci	2x SMA antenna connectors (2T2R)
Naponski priključci	1x 24-pin ATX main power connector, 1 x 8-pin ATX 12V power connector
USB-A	2 x podrška za 1 USB 2.0 port, 1 x podrška za 1 USB 5Gbps port
USB-C	1 x podrška za 1 USB 20Gbps port
Audio	1x Front panel audio, 1x Front panel header
Ostali priključci	1 x Clear CMOS jumper, 1 x Trusted Platform Module (TPM), 4 x SATA 6Gb/s, 1 x RGB LED strip header, 1 x CPU fan header, 1x CPU fan/water cooling pump header, 1x HDMI port, 1 x reset jumper, 2 x M.2 Socket 3, 3x addressable RGB Gen2 LED strip headers, 1 x reset button, 1 x system fan/water cooling pump headers, 3 x system fan headers
Podržane tehnologije	Q-Flash Plus, Smart Backup
Format	microATX
Dimenzije	244mm x 244mm
Prava potrošača:	36 meseci
EAN:	4719331866082

Raspoloživost robe možete proveriti pozivanjem Call Centra na 032/340-410

Cena na sajtu su iskazane u dinarima sa uračunatim porezom, a plaćanje se vrši isključivo u dinarima.

Nastojimo da budemo što precizniji u opisu proizvoda, prikazu slika i samih cena, ali ne možemo garantovati da su sve informacije kompletne i bez grešaka. Svi artikli prikazani na sajtu su deo naše ponude i ne podrazumeva da su dostupni u svakom trenutku.