

Kategorija: **AMD matične ploče**

Proizvođač: **Gigabyte**

Šifra: **B850AorusElite**

Matična ploča AM5 Gigabyte B850 Aorus Elite WIFI7

Matična ploča AM5 Gigabyte B850 Aorus Elite WIFI7 DDR5 HDMI/M.2

Maloprodajna cena: 36.990,00 RSD

Web cena: 34.990,00 RSD

Ušteda: 2.000,00 RSD

Specifikacija

Model	Gigabyte B850 AORUS ELITE WIFI7 AM5 DDR5 ATX Matična ploča
Procesorsko podnožje (Socket)	AMD Socket AM5
Skup čipova (Chipset)	AMD B850
Podrška za procesore	AMD Ryzen 9000 Series Processors AMD Ryzen 8000 Series Processors AMD Ryzen 7000 Series Processors
Tip memorije (RAM)	DDR5
Broj memorijskih slotova	4x 288-Pin DDR5
Podrška za memorije	Support for DDR5 8200(O.C.) / 8000(O.C.) / 7950(O.C.) / 7900(O.C.) / 7800(O.C.) / 7600(O.C.) / 7000(O.C.) / 6800(O.C.) / 6600(O.C.) / 6400(O.C.) / 6200(O.C.) / 6000(O.C.) / 5800(O.C.) / 4400 MT/s memory modules. 4 x DDR5 DIMM sockets supporting up to 256 GB (64 GB single DIMM capacity) of system memory. Dual channel memory architecture
Podrška za grafiku - portovi	Integrated Graphics Processor with AMD Radeon Graphics support: - 1 x DisplayPort, supporting a maximum resolution of 3840x2160 144Hz Support for DisplayPort 1.4 version and HDR. - 1 x Front HDMI port, supporting a maximum resolution of 1920x1080 30Hz Support for HDMI 1.4 version
Slotovi za proširenja	1 x PCI Express x16 slot (PCIEX16), integrated in the CPU: AMD Ryzen 9000/7000 Series Processors support PCIe 5.0 x16 mode AMD Ryzen 8000 Series-Phoenix 1 Processors support PCIe 4.0 x8 mode AMD Ryzen 8000 Series-Phoenix 2 Processors support PCIe 4.0 x4 mode The PCIEX16 slot can only support a graphics card or an NVMe SSD. If only one graphics card is installed, please ensure to install it in the PCIEX16 slot. Chipset: - 2 x PCI Express x16 slots, supporting PCIe 3.0 and running at x1(PCIEX1_1, PCIEX1_2)
M.2 portovi	3x M.2 Socket 3

Čuvanje podataka - portovi	<p>1 x M.2 connector (M2A_CPU), integrated in the CPU, supporting Socket 3, M key, type D SSDs: AMD Ryzen 9000/7000 Series Processors support PCIe 5.0 x4/x2 SSDs AMD Ryzen 8000 Series-Phoenix 1 Processors support PCIe 4.0 x4/x2 SSDs AMD Ryzen 8000 Series-Phoenix 2 Processors support PCIe 4.0 x4/x2 SSDs 1 x M.2 connector (M2B_CPU), integrated in the CPU, supporting Socket 3, M key, type D SSDs: AMD Ryzen 9000/7000 Series Processors support PCIe 4.0 x4/x2 SSDs AMD Ryzen 8000 Series-Phoenix 1 Processors support PCIe 4.0 x4/x2 SSDs AMD Ryzen 8000 Series-Phoenix 2 Processors support PCIe 4.0 x2 SSDs 1 x M.2 connector (M2C_SB), integrated in the Chipset, supporting Socket 3, M key, type D PCIe 4.0 x4/x2 SSDs 4 x SATA 6Gb/s connectors RAID 0, RAID 1, RAID 5, and RAID 10 support for NVMe SSD storage devices</p>
SATA portovi	4x SATA 6Gb/s
LAN	Realtek 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps)
Bežična mreža	Realtek Wi-Fi 7 RTL8922AE - 802.11a, b, g, n, ac, ax, be, supporting 2.4/5/6 GHz carrier frequency bands - Support for 11be 160MHz wireless standard(Actual data rate may vary depending on equipment.)
Bluetooth	5.4
Zvuk (Audio)	Realtek Audio CODEC High Definition Audio 2/4/5.1/7.1-channel
USB portovi	<p>CPU: - 1 x USB Type-C port on the back panel, with USB 3.2 Gen 2 support - 2 x USB 3.2 Gen 2 Type-A ports (red) on the back panel CPU+USB 2.0 Hub: - 4 x USB 2.0/1.1 ports on the back panel Chipset: - 1 x USB Type-C port with USB 3.2 Gen 2x2 support, available through the internal USB headers - 3 x USB 3.2 Gen 1 ports (1 port on the back panel, 2 ports available through the internal USB headers) - 4 x USB 2.0/1.1 ports available through the internal USB headers Chipset+USB 3.2 Gen 1 Hub: - 4 x USB 3.2 Gen 1 ports on the back panel</p>
Konektori na zadnjoj strani	1 x DisplayPort 1 x Q-Flash Plus button 4 x USB 2.0/1.1 ports 1 x USB Type-C port, with USB 3.2 Gen 2 support 5 x USB 3.2 Gen 1 ports 1 x RJ-45 port 2 x USB 3.2 Gen 2 Type-A ports (red) 2 x antenna connectors (2T2R) 2 x audio jacks 1 x optical S/PDIF Out connector

Unutrašnji konektori	<ul style="list-style-type: none"> 1 x 24-pin ATX main power connector 1 x 8-pin ATX 12V power connector 1 x 4-pin ATX 12V power connector 1 x CPU fan header 1 x CPU fan/water cooling pump header 3 x system fan headers 1 x system fan/water cooling pump header 3 x addressable RGB Gen2 LED strip headers 1 x RGB LED strip header 3 x M.2 Socket 3 connectors 4 x SATA 6Gb/s connectors 1 x front panel header 1 x front panel audio header 1 x USB Type-C header, with USB 3.2 Gen 2x2 support 1 x USB 3.2 Gen 1 header 2 x USB 2.0/1.1 headers 1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0/GC- 1 x HDMI port 1 x power button 1 x reset button 1 x reset jumper 1 x Clear CMOS jumper
Posebne mogućnosti	<ul style="list-style-type: none"> Support for GIGABYTE Control Center (GCC) Support for Q-Flash Support for Q-Flash Plus Support for Smart Backup Voltage detection Temperature detection Fan speed detection Water cooling flow rate detection Fan fail warning Fan speed control
Operativni sistem	Windows 11
BIOS	<ul style="list-style-type: none"> 1 x 256 Mbit flash Use of licensed AMI UEFI BIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
Format	ATX

Raspoloživost robe možete proveriti pozivanjem Call Centra na 032/340-410

Cena na sajtu su iskazane u dinarima sa uračunatim porezom, a plaćanje se vrši isključivo u dinarima.

Nastojimo da budemo što precizniji u opisu proizvoda, prikazu slika i samih cena, ali ne možemo garantovati da su sve informacije kompletne i bez grešaka. Svi artikli prikazani na sajtu su deo naše ponude i ne podrazumeva da su dostupni u svakom trenutku.